



1. DisplayPort	3. Type-C
2. HDMI1.4	4. Power connector

PERFORMANCE

Panel

Panel

4-side Ultra Thin, In-Plane Switching

Backlight

LED

Display Size

23.8 inches

Max View Area

- Active Area: 527.0x296.5 mm
- Screen Dimension: 535x310.1 mm

Resolution

1920x1080

Aspect Ratio

16:9

Brightness 250

cd/m²

Contrast Ratio

- Contrast Ratio(Typical): 1500:1
- Dynamic Contrast Ratio(Typical): 3000000:1

View Angle(H/V)

Horizontal:178°,Vertical:178°

Response Time

- Extreme Mode: 4ms GtG
- Fusion B24h Jun 2026

Fusion Station W4

- Normal Mode: 6ms GtG

Refresh Rate

48Hz-120Hz

Color Support

16.7 Million

Color Depth

8-bit (6-bit+FRC)

Screen Surface Treatment

Anti-glare

Operating System

Operating System

- Windows®11 Support
- Windows®10 Support

Speakers

Speaker Options

Power Supply

Power Consumption

- Typical/Max:12W/66W
- Sleep/Off mode:<0.5W
- Switch-off Mode: <0.3W
- Internal Power Supply

Voltage Required

AC 100 to 240V (50-60Hz)

DESIGN

Bezel Width

- Side:2.0 mm
- Top:2.0 mm
- Bottom:10.5 mm

Dimensions(WxDxH)^[1]

Models	Dimensions
Lowest Position	539.8x190.0x350.8mm(21.25x7.48x13.81 inches)
Highest Position	539.8x190.0x505.8mm(21.25x7.48x19.91inches)
Head Only	539.8x45.3x314.8mm(21.25x1.78x12.39inches)

Packaging Dimensions (WxDxH)

734.0x112.0x422.0mm(28.90x4.41x16.61 inches)

Weight^[2]

Models	Weight
Monitor With Stand	5.1kg(11.2lbs)*
Monitor Head Only	3.0kg(6.6lbs)*

Packaging Weight

7.3kg(16.1 lbs)

Mounting

Supports VES Amount 100x100mm

Stand

Supports-5°to+23.5°tilt, left & right 45°swivel,-90°to+90°pivot,up to 155 mm lift

In the Box

- Monitor with stand
- 1xDP cable
- 1xHDMI®cable*

Fusion Station W4

- 1xUSB Type-C
 - 1xPowercable(1.8m)
 - Quickset up guide
-

CONNECTIVITY

Ports^[1]

Rear Ports

- 1xUSB-C
 - 1xHDMI@1.4,supports 1920x1080@ 120Hz
 - 1xDisplayPort™1.2
-

SECURITY&PRIVACY

Security

Physical Locks

Kensington® Nano Security Slot

SERVICE

Warranty

Base Warranty

- 1-year limited warranty
- 3-years limited warranty

OPERATINGR EQUIREMENTS

Operating Environment

Temperature

Operating: 0°C to 40°C (32°F to 104°F) Storage:
-20°C to 60°C (-4°F to 140°F) Transport:-
20°Cto60°C(-4°Fto140°F)